DAY and TIME		COURS	£	SUBJECT
DAY-1 10.30 am to 12.30 pm SESSION: FORENOON	co	C/M.Tech/I urses offer J/UVCE/U	red by	TEXTILE TECHNOLOGY
MAXIMUM MARKS		DURATION MAXIMUM		M TIME FOR ANSWERING
100	150 MIN	0 MINUTES		120 MINUTES
MENTION YOUR PG	CET NO.	QUESTION BO		BOOKLET DETAILS
		VERSION	CODE	SERIAL NUMBER
		A -	2	140034

DOs:

- Check whether the PGCET No. has been entered and shaded in the respective circles on the OMR answer sheet. 1.
- Ensure whether the circles corresponding to course and the specific branch have been shaded on the OMR answer sheet.
- This Question Booklet is issued to you by the invigilator after the 2nd Bell i.e., after 10.25 a.m.
- The Serial Number of this question booklet should be entered on the OMR answer sheet.
- The Version Code of this question booklet should be entered on the OMR answer sheet and the respective circles should also be shaded completely.
- Compulsorily sign at the bottom portion of the OMR answer sheet in the space provided. 6.

DON'Ts:

- THE TIMING AND MARKS PRINTED ON THE OMR ANSWER SHEET SHOULD NOT BE DAMAGED / MUTILATED / SPOILED.
- The 3rd Bell rings at 10.30 a.m., till then; 2.
 - Do not remove the paper seal / polythene bag of this question booklet.
 - Do not look inside this question booklet.
 - Do not start answering on the OMR answer sheet.

IMPORTANT INSTRUCTIONS TO CANDIDATES

- This question booklet contains 75 (items) questions and each question will have one statement and four answers. 1. (Four different options / responses.)
- After the 3rd Bell is rung at 10.30 a.m., remove the paper seal / polythene bag of this question booklet and check that this booklet does not have any unprinted or torn or missing pages or items etc., if so, get it replaced by a complete test booklet. Read each item and start answering on the OMR answer sheet.
- During the subsequent 120 minutes:
 - Read each question (item) carefully.
 - Choose one correct answer from out of the four available responses (options / choices) given under each question / item. In case you feel that there is more than one correct response, mark the response which you consider the best. In any case, choose only one response for each item.
 - Completely darken / shade the relevant circle with a BLUE OR BLACK INK BALL POINT PEN against the question number on the OMR answer sheet.
- Use the space provided on each page of the question booklet for Rough Work. Do not use the OMR answer sheet for the same.
- After the last Bell is rung at 12.30 pm, stop marking on the OMR answer sheet and affix your left hand thumb impression on the OMR answer sheet as per the instructions.
- Hand over the OMR ANSWER SHEET to the room invigilator as it is.
- After separating the top sheet, the invigilator will return the bottom sheet replica (Candidate's copy) to you to carry home for self-evaluation.
- Preserve the replica of the OMR answer sheet for a minimum period of ONE year.
- Only Non-programmable calculators are allowed.

Marks Distribution

50 QUESTIONS CARRY ONE MARK EACH (1 TO 50) 25 QUESTIONS CARRY TWO MARKS EACH (51 TO 75) PART-2

[Turn Over



TEXTILE TECHNOLOGY PART – 1

Each question carries one mark.

 $50\times1=50$

1.	Mino	or cleaning points in blow room are		
	(A)	Openers	(B)	Beaters
	(C)	Lattices	(D)	Cages
2.	Tras	h to lint ratio in blow room waste is	5	
	(A)	70:30	(B)	90:10
	(C)	80:20	(D)	60 : 40
3.	The	cylinder speed in comber is express	sed in	
	(A)	NPM	(B)	RPM
	(C)	mts/min	(D)	mm/min
4.	Fibr	e to fibre separation is achieved in		
	(A)	Draw frame	(B)	Comber
	(C)	Card	(D)	Speed frame
5.	Con	nbing reduces neps by		
	(A)	50%	(B)	70%
	(C)	80%	(D)	25 – 40%
6.	Step	p cleaner consists of		
	(A)	6 – 8 cylinders	(B)	14 cylinders
	(C)	20 cylinders	(D)	24 cylinders

Ope	n end spinning is used to produce		
(A)	Finer count yarns	(B)	Fancy yarns
(C)	Uniform yarns	(D)	Highly twisted yarns
Repo	co spinning produces		
(A)	Core spun yarns	(B)	Self twist yarns
(C)	Cover spun yarns	(D)	Siro yarns
Con	e angle required to wind knit cones	on dru	ım winding machine is
(A)	20 15'	(B)	30 10'
(C)	200 15'	(D)	9 ⁰ 15'
The	stretch allowed for cotton warp on	multic	ylinder sizing machine is
(A)	5%	(B)	2%
(C)	6%	(D)	10%
The	air pressure required on Air – jet lo	om at	the time of west insertion is
(A)	10 bar	(B)	6 bar
(C)	20 bar	(D)	30 bar
The	torsion rod picking is generally use	ed on	
(A)	Rapier looms	(B)	Air – jet looms
(C)	Multiphase looms	(D)	Sulzer looms
The			g the back set of heald shaft is more than bet operating the front set of heald shafts.
(A)	5%	(B)	10%
(C)	23%	(D)	50%
	(A) (C) Report (A) (C) Conc (A) (C) The (A) (C) The (A) (C) The (A) (C)	Repco spinning produces (A) Core spun yarns (C) Cover spun yarns Cone angle required to wind knit cones (A) 20 15' (C) 200 15' The stretch allowed for cotton warp on (A) 5% (C) 6% The air pressure required on Air – jet lo (A) 10 bar (C) 20 bar The torsion rod picking is generally use (A) Rapier looms (C) Multiphase looms The stroke of the tappet which is op compared to the stroke of the compared to the compared to the stroke of the compared to the stroke of the compared to the co	(A) Finer count yarns (B) (C) Uniform yarns (D) Repco spinning produces (A) Core spun yarns (B) (C) Cover spun yarns (D) Cone angle required to wind knit cones on dru (A) 2º 15' (B) (C) 20º 15' (D) The stretch allowed for cotton warp on multic (A) 5% (B) (C) 6% (D) The air pressure required on Air – jet loom at (A) 10 bar (B) (C) 20 bar (D) The torsion rod picking is generally used on (A) Rapier looms (B) (C) Multiphase looms (D) The stroke of the tappet which is operating compared to the stroke of the tappet (B)

14.	Rasc	hel is a	knitting mach	ine.				
	(A)	Weft		(B)	Warp			
	(C)	Flat		(D)	Triaxial			
15.	Cone	test is genera	illy used to test					
	(A)	Woven fabri	cs.				,	
	(B)	Warp knitted	l fabrics.					
	(C)	Non woven	fabrics.					
	(D)	Braided fabr	ics.					
16.	The	enzymes used	for desizing of cotto	n are				
	(A)	Fructases		(B)	Xylanases			
	(C)	Amylases		(D)	Pectinases			
17.	Liqu	id ammonia n	nercerization is carri	ed out	at			
	(A)	75 °C		(B)	40 °C			
	(C)	– 10 °C		(D)	-20 °C			
18.	Synt	thetic fibres ar	e generally bleaohed	l by				
	(A)	Sodium hyp	ochlorite					
	(B)	Calcium hyp	oochlorite			•		
	(C)	Sodium chlo	orate/chlorite			-		
	(D)	Potassium d	ichromate					
			Space	For Ro	ugh Work			

19.	As tl	he crystallite orientation in fibres in	crease	es, the dye uptake
	(A)·	Remains same		
	(B)	Increases		
	(C)	Decreases		
	(D)	Increases and then decreases		
20.	Acry	vlic fibres are generally dyed by		
	(A)	Acid dyes		
	(B)	Direct dyes		
	(C)	Metal complex dyes		
	(D)	Basic dyes		
21.	Redu	ucing agent used in sulphur dyeing	is	
	(A)	Sodium perborate		
	(B)	Calcium metaphosphate		
	(C)	Sodium sulphide		
	(D)	Sodium phosphate		
22.	Afte	r treatments given to direct dyed go	ods in	nprove their
	(A)	Crystallinity	(B)	Size of dye particles inside the fibre
	(C)	Absorbency	(D)	Hydrophobicity
23.	Gene	erally knitted fabrics are dyed using	5	
	(A)	Jet dyeing machine		
	(B)	Jigger dyeing machine		
	(C)	HT – HP beaker dyeing machine		
	(D)	Soft flow dyeing machine		
-		Space F	or Roi	igh Work

24.	the	rating range for light fastness prope	rty is	
	(A)	1 – 5	(B)	1 – 6
	(C)	1 – 4	(D)	1 – 8
25.	In di	scharge printing discharging of gro	und co	olour is carried out by
	(A)	Sequesting agents	(B)	Reducing agents
	(C)	Surfactants	(D)	De – lustering agents
			-	
26.	Wet	transfer printing makes use of		
	(A)	Disperse dyes	(B)	Pigment colours
	(C)	Water – soluble dyes	(D)	Vat dyes
27.	DM	DHEU is a popular		
	(A)	Water proofing agent	(B)	Soil releasing agent
	(C)	Anticreasing agent	(D)	Moth proofing agent
28.	Hear	t setting of polyester is carried out a	ıt	
	(A)	90 – 110 °C	(B)	60 – 70 °C
	(C)	200 – 220 °C	(D)	120 − 130 °C
29.	Biop	polishing agents used for cotton and	l other	garments are
	(A)	Cellulases	(B)	Trypsin
	(C)	Alcaleses	(D)	Rapidases

30.	If D	is the fibre diameter, air flow rate t	hrough	a plug of fibres is proportional to
	(A)	D	(B)	D^2
	(C)	1/D	(D)	1/D ²
31.		spun yarn, as the number of fibrularity	res in	the cross section increases, the basic yarn
	(A)	increases		
	(B)	decreases		
	(C)	· unaffected		
	(D)	initially decreases & then increase	es	
32.	For a	a known growth, the micronaire val	lue of	cotton fibre is the measure of
	(A)	Fibre fineness	(B)	Fibre strength
	(C)	Fibre maturity	(D)	Fibre length
33.		h hairiness index obtained using hat length of protruding hairs (in cm)		s sensor on uster evenness tester refers to the arn length of
	(A)	1 mm	(B)	10 mm
	(C)	100 mm	(D)	1000 mm
34.	Stele	ometer works on the following prin	ciple (of loading :
	(A)	CRT	(B)	CRE
	(C)	CRL	(D)	Both CRT & CRE
		Space F	or Ro	ngh Work

	.	Space I	or Ro	ugh Work			
	(C)	Arvind mills	(D)	Raymond fabrics			
	(A)	Reliance apparels	(B)	Madhura garments			
39.	Pete	er England is a brand name of					
	(C)	low	(D)	cross			
	(A)	medium	(B)	high			
38.	Trar	m is twisted yarn.	<i>-</i>				
	(D)	Flat croissure					
	(C)	Chambon type croissure					
	(B)	Semicircular type croissure					
	(A)	Traveletta type croissure		•			
37.	Mul	tiend reeling machine uses					
		•					
	(C)	evenness of silk	(D)	neatness of silk			
	(A)	strength of silk	(B)	abrasion of silk			
36.	Serip	plane instrument is used for measur	ing				
	(D)	conditioning the cocoons for bette	r reeli	ng.			
	(C) killing the pupa inside the cocoon.						
	(B) sorting of cocoons according to their shape.						
	(A)	sorting of cocoons according to th	eir siz	e.			
35.	Coco	oon riddling is the process of					

40.	Func	ctionality (f) in case of tri-bi function	nal mo	onomers is
	(A)	2.0	(B)	1.0
	(C)	4.5	(D)	2.5
41.		each reactant minimum oflensation polymerisation.	fun	actional groups are required for conducting
	(A)	1	(B)	2
	(C)	3	(D)	4
	. Tri			
42.	The	commercial textile grade acrylic fib	ore is	
	(A)	a homopolymer of acrylonitrile.		·
	(B)	a homopolymer of acrylamide.		
	(C)	a copolymer containing atleast 85	% PA	N moiety.
	(D)	a copolymer containing 85% Poly	acryla	mide moiety.
43.	Com	amercial grade polypropylene is		
	(A)	Isotatic	(B)	Atactic
	(C)	Syndiotactic	(D)	Smectic
44.	Jute,	, flax and ramie belong to		
	(A)	Hair fibres	(B)	Bast fibres
	(C)	Leaf fibres	(D)	Fruit fibres

45.	Mois	sture regain of Nylon fibre is in the	range	of
	(A)	2.0 - 3.0	(B)	3.5 – 4.5
	(C)	5.0 - 6.0	(D)	6.5 – 7.5
46.	The	density of polyester fibre is		
	(A)	more than that of cotton.		
	(B)	same as that of nylon.		
	(C)	more than that of nylon but less th	nan tha	t of cotton.
	(D)	more than that of polypropylene b	ut less	than that of nylon.
45	22 rt ·	1 . C4 C. II	films 9	·
47.		ch of the following is multicellular		
	(A)	Cotton	(B)	Flax
	(C)	Silk	(D)	Cupraamonium rayon
48.	Amo	ongst the following fibres, the high	est init	ial modulus is demonstrated by
	(A)	Cotton	(B)	Wool
	(C)	POY polyester	(D)	Jute
49.	Lyo	cel is a		
	(A)	Cellulosic fibre	(B)	Protein fibre
	(C)	Polyamide fibre	(D)	Polyester fibre
50.	The	seed percentage in KAPAS is		·
	(A)	45%	(B)	66%
	(C)	55%	(D)	70%
				

Each question carries two marks.

(A) (C) If the 110; (A) (C) If the is (A) (C)	0.14 Ne 0.16 Ne ne front roller speed of yds/min, then the draw fra 10 8 e linear density of roving 1.2 Ne 1.9 Ne	(B) (D) f draw frame ame draft is (B) (D) delivered in specific (B) (D)	0.12 Ne 0.18 Ne is 800 mts/min and back roller speed is 9 1 eed frame is 280 Tex then the hank of roving 1.6 Ne 2.1 Ne me is 1800 yds and twist contraction is 5%, 1710 yds 1800 yds	
(A) (C) If the control of the contr	0.14 Ne 0.16 Ne ne front roller speed of yds/min, then the draw fra 10 8 e linear density of roving 1.2 Ne 1.9 Ne length of yarn at front rothe length on bobbin is 1780 yds	(B) (D) f draw frame ame draft is (B) (D) delivered in special (B) (D) other of ring frame (B)	0.12 Ne 0.18 Ne is 800 mts/min and back roller speed is 9 1 eed frame is 280 Tex then the hank of roving 1.6 Ne 2.1 Ne me is 1800 yds and twist contraction is 5%,	
(A) (C) If the 110; (A) (C) If the is (A) (C)	0.14 Ne 0.16 Ne ne front roller speed of yds/min, then the draw fra 10 8 e linear density of roving 1.2 Ne 1.9 Ne length of yarn at front ro	(B) (D) f draw frame ame draft is (B) (D) delivered in special (B) (D) oller of ring frame draft is	0.12 Ne 0.18 Ne is 800 mts/min and back roller speed is 9 1 eed frame is 280 Tex then the hank of roving 1.6 Ne 2.1 Ne me is 1800 yds and twist contraction is 5%,	
(A) (C) If the 110; (A) (C) If the is (A) (C)	0.14 Ne 0.16 Ne ne front roller speed of yds/min, then the draw fra 10 8 e linear density of roving 1.2 Ne 1.9 Ne	(B) (D) f draw frame ame draft is (B) (D) delivered in specific (B) (D)	0.12 Ne 0.18 Ne is 800 mts/min and back roller speed is 9 1 eed frame is 280 Tex then the hank of roving 1.6 Ne 2.1 Ne	
(A) (C) If the 110 (A) (C) If the is (A)	0.14 Ne 0.16 Ne ne front roller speed of yds/min, then the draw fra 10 8 e linear density of roving	(B) (D) f draw frame ame draft is (B) (D) delivered in specific (B)	0.12 Ne 0.18 Ne is 800 mts/min and back roller speed is 9 1 eed frame is 280 Tex then the hank of roving 1.6 Ne	
(A) (C) If the 110 (A) (C) If the is (A)	0.14 Ne 0.16 Ne ne front roller speed of yds/min, then the draw fra 10 8 e linear density of roving	(B) (D) f draw frame ame draft is (B) (D) delivered in specific (B)	0.12 Ne 0.18 Ne is 800 mts/min and back roller speed is 9 1 eed frame is 280 Tex then the hank of roving 1.6 Ne	
(A) (C) If the 110 (A) (C) If the	0.14 Ne 0.16 Ne ne front roller speed of yds/min, then the draw fra 10 8 e linear density of roving	(B) (D) f draw frame arme draft is (B) (D) delivered in special	0.12 Ne 0.18 Ne is 800 mts/min and back roller speed is 9 1 eed frame is 280 Tex then the hank of roving	
(A) (C) If th 110; (A) (C)	0.14 Ne 0.16 Ne ne front roller speed of yds/min, then the draw fra 10	(B) (D) f draw frame ame draft is (B) (D)	0.12 Ne 0.18 Ne is 800 mts/min and back roller speed is 9 1	
(A) (C) If th 110 (A) (C)	0.14 Ne 0.16 Ne ne front roller speed of yds/min, then the draw fra 10	(B) (D) f draw frame ame draft is (B) (D)	0.12 Ne 0.18 Ne is 800 mts/min and back roller speed is 9 1	
(A) (C) If th 110; (A)	0.14 Ne 0.16 Ne ne front roller speed of yds/min, then the draw fra	(B) (D) f draw frame ame draft is (B)	0.12 Ne 0.18 Ne is 800 mts/min and back roller speed is	
(A) (C) If th	0.14 Ne 0.16 Ne ne front roller speed of yds/min, then the draw fra	(B) (D) f draw frame ame draft is	0.12 Ne 0.18 Ne is 800 mts/min and back roller speed is	
(A) (C) If th	0.14 Ne 0.16 Ne ne front roller speed of	(B) (D)	0.12 Ne 0.18 Ne is 800 mts/min and back roller speed is	
(A) (C)	0.14 Ne 0.16 Ne	(B) (D)	0.12 Ne 0.18 Ne	
(A)	0.14 Ne	(B)	0.12 Ne	
			0.12 Ne	
If the	e length at card cliver is 6	vds and weight	18 33 grains, then the nank of sliver is	
` ,		•	257 when the best of discourse	
• •		(D)	75%	
	-	(B)	65%	
			om the conton mixing having 670 trash, then	
100		in blanv raam fi	om the cotton mixing having 8% trash then	
` /	2 -			
(C)	Alternate copolymers			
		,		
Mixi	ng of two polymer melts	yields		
(D)	Density measurement			
(C)	Optical microscopy			
(B)	Burning test			
(A)	Melting point test			
Nylo	n – 6 & Nylon – 66 filam	ents can be disti	nguished by	
	A) B) C) D) Mixi A) B) C) D) f 6 :	A) Melting point test B) Burning test C) Optical microscopy D) Density measurement Mixing of two polymer melts: A) Block copolymers B) Random copolymers C) Alternate copolymers D) Polymer blends f 6 gms of trash is extracted the blow room cleaning efficient A) 85% C) 95%	A) Melting point test B) Burning test C) Optical microscopy D) Density measurement Mixing of two polymer melts yields A) Block copolymers B) Random copolymers C) Alternate copolymers D) Polymer blends f 6 gms of trash is extracted in blow room fine blow room cleaning efficiency is A) 85% (B) C) 95% (D)	B) Burning test C) Optical microscopy D) Density measurement Mixing of two polymer melts yields A) Block copolymers B) Random copolymers C) Alternate copolymers D) Polymer blends f 6 gms of trash is extracted in blow room from the cotton mixing having 8% trash, then the blow room cleaning efficiency is A) 85% (B) 65%

58.	Weft	cutters are used in		•
	(A)	Pirn winding machine	(B)	Warping machine
ı	(C)	Conventional looms	(D)	Shuttleless looms
59.	The c	lisadvantage of the rigid rapier sys	tem is	
	(A)	Higher cost		
	(B)	Unsuitability to weave light wt fal	brics	
	(C)	Increased floor space		
	(D)	High maintenance		
60.	Then	mosol dyeing of PET uses		
	(A)	Exhaustion dyeing principle	(B)	Pad-dry-cure principle
	(C)	Dye-exhaust method	(D)	Batch-pad-dry principle
61.	THP	C is a very popular		
	(A)	Fixing agent	(B)	Fire proofing agent
	(C)	Rot proofing agent	(D)	Anti-creasing agent
62.	Addi	ition of sodium carbonate as affixing	ng ager	nt is added in reactive dyeing at
	(A)	The beginning of dyeing		
	(B)	Middle of dyeing		
	(C)	End of dyeing	•	
	(D)	It is not added at all		
63.		ier of a cotton fibre with a matur oximately	ity rat	io of 0.9 and micronaire value of 4 will be
	(A)	1.0	(B)	1.3
	(C)	1.6	(D)	1.9
64.	Leng	gth of 2 kg of 180 denier polyester	yarn is	3
	(A)	90 km	(B)	100 km
	(C)	180 km	(D)	360 km

65.	AQL system inspection is related to						
	(A)	Fabric inspection					
	(B)	Garment inspection					
	(C)	Sewing thread					
	(D)	Support materials inspection					
66.	The rpm of the sewing machine is equal to the						
00.	(A) Speed of the needle bar						
	(B) No. of stitches / min						
	(C) Speed of cylinder(D) The material fed to sewing point						
	(D)	The material feat to sewing point					
67.	Projected area of a 30 cm dia fabric specimen paced on 20 cm dia support plate of drape tester is 302 cm ² . Drape coefficient for this fabric is						
	(A)	0.47 (B) 0.57					
	(C)	0.67 (D) 0.77					
68.	Garments are dyed on						
	(A)	Jiggers					
	(B) Winches						
	(C) Horizontal paddle dyeing machines						
	(D) Jet dyeing machines						
69.	Ban	d knife cutting machine is recommended					
٠,٠	(A) to cut small pattern pieces like collars and cufs.						
	(B) to cut large pattern pieces.						
	(C) to make edge finishings.						
	(D)	to cut fabric rolls.					
	Space For Dough Work						

70.	Theo	Theoretical maximum extent of reaction during polymerization of bi – bi functional monomers is (assuming $Dp = \infty$)					
	(A)	40%	(B)	80%			
	(C)	90%	(D)	100%			
71.	1. The volume of breaking length in km (RKM) of a filament is numerically equa						
	(A)	Tenacity in N/Tex	(B)	Breaking load in N			
	(C)	Tenacity in gf/Tex	(D)	Breaking load in gf			
72.	With increase in RH from 0 to 100% the tensile properties of cotton fibres change such that						
	 (A) modulus & strength increases, extensibility decreases. (B) modulus decreases, strength & extensibility increases. (C) modulus, tenacity as well as extensibility increases. (D) modulus & tenacity increases, extensibility remains same. 						
73.		In the manufacture of PET, the principal compounds involved during polycondensation step is / are					
	(A)	MEG & DMT	(B)	EG & PTA			
	(C)	DBT	(D)	DGT			
74.	74. If the present moisture regain (R) of a fibre is 8, its percent moisture content						
		7.4	(B)	7.2			
	(C)	7.6	(D)	7.0			
<i>7</i> 5.	5. Water is added to caprolactum during the polymerization of nylon -6 . Its pr						
-	(A)	Solvent	(B)	Catalyst			
	(C)	Heat sink	(D)	Stabiliser			
				. <u></u>			
	Space For Rough Work						

16

A-2